

Puller



The CM Puller is designed for heavy-duty construction and industrial applications. Used to pull, lift, drag or stretch, it features:


- Tough aluminum alloy construction and powder coat finish
- Weatherproof for outdoor service
- Simple construction with fewer parts for ease of maintenance and lower inventories
- Hoistaloy hardened steel link type load chain for strength, long wear life and flexibility
- Weatherized Weston-type automatic braking system for positive load control
- Easy, one-hand operation and control — only 58 pounds of pull required for ¾ ton model capacity
- Forged upper and lower hooks with latches standard
- Free wheeling for fast and easy attachment to load
- Upper and lower Latchlok hooks available for all capacities
- Optional Load Limiter protection device stops transmission of lever forces protecting against dangerous overload
- Optional anchor sling simplifies attachment to allow anchor hook to swivel in tight space applications (¾ & 1½ ton units only)
- Optional Load Sentry warns of overload condition
- Optional zinc-plated chain available
- Unlimited lift
- Lifetime warranty
- Metric rated
- Made in U.S.A.



Optional Load Limiter



Optional anchor sling (¾ and 1½ ton)



Latchlok type hook



¾ ton

Puller specifications - standard unit

| Rated capacity* (tons) | Product code | Standard lift† (ft.) | Pull to lift full loads (lbs.) | Minimum distance between hooks (in.) | Lever length (in.) | Reeving | Hook throat openings (in.) | Approx. shipping weight (lbs.) |
|------------------------|--------------|----------------------|--------------------------------|--------------------------------------|--------------------|---------|--------------------------------|--------------------------------|
| ¾ | 4043 | 5 | 58 | 10¾ | 21¼ | 1 | 1½ | 16 |
| 1½ | 4045 | 5 | 89 | 14¼ | 21¼ | 1 | 1½ | 26 |
| 3 | 4047 | 5 | 95 | 16 ¹⁵ / ₁₆ | 21¼ | 2 | 1 ⁷ / ₃₂ | 38 |
| 6 | 4050 | 5 | 96 | 21¾ | 21¼ | 4 | 1¾ | 73 |

† Can be supplied with lifts longer than 5 feet

Optional kits

| Rated capacity* (tons) | Load Limiter | | Load Sentry kit | | | Anchor sling kit | |
|------------------------|--------------|--------------------------------|-----------------|--------------------|--------------------------------|------------------|--------------------------------|
| | Product code | Approx. shipping weight (lbs.) | Product code | Lever length (in.) | Approx. shipping weight (lbs.) | Product code | Approx. shipping weight (lbs.) |
| ¾ | 4190 | 8¼ | 4096 | 23¾ | 4½ | 4071 | 2 |
| 1½ | 4191 | 8¼ | 4098 | 23¾ | 4½ | 4072 | 4¾ |
| 3 | 4191 | 8¼ | 4098 | 23¾ | 4½ | — | — |
| 6 | 4191 | 8¼ | 4098 | 23¾ | 4½ | — | — |